

PIXELIDY-S (PX130)



The “**PIXELIDY**” shares the same optical characteristics as the rest of the range. These include a high quality white LED with a high colour rendering index for a rich, saturated light and a narrow 10° lens that produces a fine, powerful beam for precise spot lighting.

Its **light weight** and small size make it easy to fit into the most confined spaces. Its simple, **functional design** means it’s discreet and easy to overlook in any environment. It can be used in a wide range of applications including stages, hotels and restaurants, shops, museums and galleries, TV studios and cinemas.

The projector’s theatre-inspired **yoke** provides 360° pan and tilt adjustment and ensures a secure hold. The bracket is removable, allowing the projector to be remounted on other hanging accessories or set elements.

Its **IP63 rating** makes it impervious to dust and water. It can be used outdoors when covered.


Optional accessories are available:

- Holographic filters to change beam width (spot, flood, asymmetric)
- Halo shield to reduce glare.
- Magnetic base for quick installation on a metal stand.



Technical specifications

GENERAL



Dimensions	58mm(w) x 51mm(h) x 31mm(d)
Weight	58gr (touring version: 70gr)
Materials	Black anodised aluminium and black ABS
Cooling	Passive
Cable	2 pins M6 male plug ; Length : 500mm 2x0.3mm ² Nylon PA66 flame resistance material
Operating temperature	0 – 45°C
Warranty	1 year
IP rating	IP63

LIGHT

Type of LED	LUMILEDS Luxeon TX or Z
Number of LEDs	1
Colour temperature(K)	2700 ; 3000 ; 3500 ; 4000 ; 5700
IRC	Min 90 / Typ 92
Step Macadam	3
Luminiuous efficacy	102lm/W @ 3000K
Optics	TIR lense / 10 ° / Ø21,6mm / PMMA clear

ELECTRICAL

Voltage	3VDC
Current	700 mA constant current
Power	2,1W

STANDARDS

CE - RoHS - REACH
EN62368-1:2020 +A11 ; EN60598-2-1:2021 ;
EN60598-2-17 :2018 ; EN62471:2008

References

PRODUCT

Reference	Description
PX130	Bare Pixelidy-S
PX131	Bare Pixelidy-S + full accessory kit

ACCESSOIRES

Reference	Description
PX230	Black anodised aluminium halo cover for Pixelidy-S
PX232	Magnetic base for Pixelidy-S
PX233/C	Set of 6 circular holographic filters, 20°
PX233/A	Set of 6 asymmetrical holographic filters, 15x45°

Cables

Reference	Description
PX321/0,5	M6 cable for Pixelidy ; 1 male plug + 1 female plug ; length 0,5m
PX321/1	Length 1m
PX321/2,5	Length 2,5m
PX321/5	Length 5m